


(19)  Canadian
Intellectual Property
Office

An Agency of
Industry Canada

Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

(11) CA 2 348 114 (13) A1

(40) 17.11.2002
(43) 17.11.2002

(12)

(21) 2 348 114

(51) Int Cl.7: H04L 29/06, H04M 11/06,
H04N 1/32

(22) 17.05.2001

(71)

MEDIATRIX TELECOM INC.,
4229 rue Gariock, SHERBROOKE, Q1 (CA).

BERARD, FRANCOIS (CA).

(74)

GOUDREAU GAGE DUBUC

(72)

(54) TELEPHONE IP MULTIPROTOCOLE
(54) MULTI-PROTOCOL IP PHONE

(57)

Multi-protocol IP phone, IP fax and wiretap
are described herein.



Office de la Propriété
Intellectuelle
du Canada
Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office
An agency of
Industry Canada

CA 2348114 A1 2002/11/17

(21) 2 348 114

(12) DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION
(13) A1

(32) Date de dépôt/Filing Date: 2001/05/17

(41) Mise à la disp. pub./Open to Public Insp.: 2002/11/17

(51) Cl. Int./Int. Cl.: H04L 29/06, H04N 1/32, H04M 11/06

(71) Demandeur/Applicant:
MEDIATRIX TELECOM INC., CA

(72) Inventeur/Inventor:
BERARD, FRANCOIS, CA

(74) Agent: GOUTREAU GAGE DUBUC

(54) Titre : TELEPHONE IP MULTIPROTOCOLE

(54) Title: MULTI-PROTOCOL IP PHONE

(57) Abrégé/Abstract:

Multi-protocol IP phone, IP fax and wireless are described herein.

Canada

<http://siptic.gc.ca> • Ottawa-Hull K1A 0G9 • help@siptic.gc.ca

OPIC CIPC 194

OPIC



CIPC

ABSTRACT OF THE DISCLOSURE

Multi-protocol IP phone, IP fax and wiretap are described herein.

TITLE OF THE INVENTION

MULTI-PROTOCOL IP PHONE

5 FIELD OF THE INVENTION

The present invention relates to voice over Internet protocols (VoIP). More specifically, the present invention is concerned with a multi-protocol IP phone.

10

BACKGROUND OF THE INVENTION

Voice over the Internet protocols (VoIP) enables transmission of the voice over the Internet. This technology provides an alternative and ultimately someday a replacement to public switch telephone networks (PSTN).

15

Many VoIP signalling protocols are known including for example: Session Initiation Protocol (SIP) (RFC 2543), Media Gateway Control Protocol (MGCP) (RFC 2705), Megaco Protocol (RFC 3015) and H.323.

20

Many major telephony companies are researching (and eventually deploying) more than one signalling protocol. However, signalling protocols are designed independently and usually do not have built-in translation from one to the other. Even if translators between those

25

protocols are being developed, there are potential benefits to have a device that supports multiple signalling protocols simultaneously.

Moreover, current VoIP either enable a single phone acting
5 as a peer in a peer-to-peer architecture or as a slave in a master-slave architecture. Usually, the total control of the phone implied by the master-slave architecture would make it impossible for an IP phone to simultaneously act as a slave and as a peer.

10 Indeed, on some master-slave architecture (like in MGCP or Megaco) the master knows every event occurring on the IP phone. The master also controls every signal applied on the IP phone. The problem that arises, when an MGCP IP phone wants to support a peer-to-peer protocol like SIP, is that the signals and events needed for the peer-to-
15 peer protocol conflict with those managed by the master.

For example, when a user picks up a phone implementing the MGCP to make a call, the Call-Agent (the master in a MGCP network) is notified of the "off hook" event and asks the MGCP phone to generate
20 a "dial tone" signal. If a peer-to-peer device such as a SIP User Agent, tries to call the same phone, the Call-Agent will not be aware of it since the different signalling protocols are not aware of each other. When the MGCP phone receives the SIP invitation for a call, it should start to ring. The MGCP Call-Agent does not request this "ring" signal. This would
25 usually work, but when the user will pick up the phone to answer the SIP call, the Call-Agent must not be notified of this "off hook" event because no "dial tone" signal must be applied. If the phone goes "off hook" without

10

15

25

According to a first embodiment of the present invention, there is provided a multi-protocol IP phone that is configured to simultaneously receive calls from a plurality of supported signalling protocols such as SIP, MGCP and Megaco and to make a call using any

of the supported signalling protocols. This is achieved by hiding the events and signals of one signalling protocol from the other supported signalling protocols. The segregation also applies to the media flow.

5 The signalling protocol segregation is advantageously realized through a user interface. Indeed, in addition to the traditional phone interface that includes dual tone multifrequency (DTMF) buttons, flash button, hold button, etc., the multi-protocol IP phone includes other user interface elements that allow selection, information on status and/or
10 other operation on a particular signalling protocol.

For example, a "Line Button" for each supported signalling protocol. This "Line Button" advantageously includes a light to indicate the usage of the line. In addition to the "Line Button", an IP phone, according
15 to the first embodiment of the present invention, also includes "Hold" and "Speaker" buttons that regulate the IP phone operation outside the control of the signalling protocol.

Other interface elements may also be provided to allow
20 different functions for each of the protocols implemented on the IP phone.

The IP phone may take many forms, from a device having a design similar to a traditional phone, to a software implementation on a
25 computer.

According to the first embodiment of the present invention, each protocol that is implemented on the IP phone controls a virtual IP

30

11

29

"busy tone", etc.) are advantageously memorized but not generated in the physical IP phone. The related signalling protocol doesn't know that the signals do not reach the user. If the signals have to stop before the virtual IP phone ever becomes active, the user will never know they were requested. If the virtual IP phone becomes active before the end of the signals, then the signals are applied to the physical IP phone, as they would normally be. An exception to this rule is when the signalling protocol needs the virtual IP phone to ring while it is inactive. In this case, instead of applying a normal ring to the physical IP phone, a single brief ring will be applied to the physical phone and the light of the "Line Button" associated with the signalling protocol will flash.

Few rules are required to regulate which virtual IP phone is active. Since the signalling protocols are unaware of the concept of an active virtual IP phone, they advantageously do not request the activation and deactivation of the virtual IP phones.

Some of the triggers for activation/deactivation may not even be implemented in a particular signalling protocol. The usage of "Line Button", "Hold Button" and "Speaker Button" that are often part of the user interface of a conventionally PSTN phone doesn't make sense in the signalling protocol context.

Other events that are implemented in some signalling protocols activate or deactivate a virtual IP phone as a transparent side effect. For example, when a call is received for a specific signalling protocol, the "ring" signal is requested on the appropriate virtual IP phone.

if no other virtual IP phone is active, the ringing virtual IP phone becomes active. Not only does the physical IP phone now ring, but when the user will pick up the phone, it will also automatically be in the active virtual IP phone and answer the received call. Another example of implicit activation is when the user picks up the phone and no virtual IP phone is presently active, the default virtual IP phone becomes active and receives the "off hook" event.

The combination of an active virtual IP phone and events hidden from the signalling protocols allow services such as making an MGCP call, putting it on hold to answer a received SIP call, and switching between the two without interaction between the SIP and MGCP signalling protocols.

The IP phone according to the present invention may include a virtual IP phone manager, advantageously in the form of software, to abstract the physical IP phone from each signalling protocol.

A multi-protocol IP phone, according to embodiments of the present invention, could either have a unique phone number (usable by a user of any supported signalling protocol) or have one different phone number by supported signalling protocol.

For example, in SIP, the mapping between the phone number and the IP address and port of the phone is done in a SIP Redirect Server. In MGCP and Megaco, the mapping is done through the Call-Agent. If all of these databases are independent, it is possible to have

50

10

15

20

25

(Tag Image File Format).

A multi-protocol wiretap according to the present invention would allow copying of the mixed media flow and would forward it, for example, to a server via an IP network such as the Internet. The server would advantageously be configured to backup the phone conversation and relay it upon demand to a remote computer.

Although the present invention has been described hereinabove by way of preferred embodiments thereof, it can be modified without departing from the spirit and nature of the subject invention, as defined in the appended claims.

WHAT IS CLAIMED IS:

1. A multi-protocol IP phone as described in the present application.
- 5 2. A multi-protocol IP fax as described in the present application.
3. A multi-protocol wiretap as described in the present application.

10